

SERIE RXB

RXB-610

10 X 600 X 400 mm.

10 x GN 1/1



13.650 W




250° C



109 Kg.



400 V - 50/60 Hz



CARACTERÍSTICAS features

- | | |
|--|---|
| <ul style="list-style-type: none"> ● DIMENSIONES INTERNAS: (W)490x(D)655x(H)935 mm
<i>cooking chamber dimension</i> | <ul style="list-style-type: none"> ● POTENCIA: 13.650 W
<i>power</i> |
| <ul style="list-style-type: none"> ● DIMENSIONES EXTERNAS: (W)755x(D)890x(H)1145 mm
<i>external dimension</i> | <ul style="list-style-type: none"> ● TEMPERATURA MÁXIMA: 250° C
<i>max temperature</i> |
| <ul style="list-style-type: none"> ● DISTANCIA ENTRE PARRILLAS: 80 mm.
<i>distance between trays</i> | <ul style="list-style-type: none"> ● PESO: 109 Kg.
<i>weight</i> |
| <ul style="list-style-type: none"> ● CONEXIÓN: Trifásica 3F+N+T
<i>3p + n + e three phase</i> | <ul style="list-style-type: none"> ● VOLTAJE: 400 V / 50-60 Hz
<i>Voltage</i> |

EQUIPAMIENTO equipment

- | | |
|---|---|
| <ul style="list-style-type: none"> ● Temporizador 0-120 min. + modo continuo
<i>timer 0-120 min. + continuous function.</i> ● Alarma fin de ciclo <i>Cycle end alarm</i> ● Micro de puerta <i>Door safety switch</i> ● Termostato de seguridad <i>Safety thermostat</i> | <ul style="list-style-type: none"> ● Lámpara interior <i>Halogen chamber light</i> ● Inversor de giro <i>Reversing gear</i> ● Conexión agua ¾ <i>Water connection ¾</i> ● Humedad regulable 0-100% <i>Adjustable humidity 0% - 100 %</i> ● Vidrio abatible para limpieza <i>Folding inner glass for cleaning</i> |
|---|---|

OPCIONES (PVP) options (rrp)

- CAMBIO APERTURA PUERTA: 380 €
change opening door

PVP rrp **RXB-610**